



PTO/SB/21 (08-03)
Approved for use through 07/31/2006. OMB 0651-0031
U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM (to be used for all correspondence after initial filing)	Application Number	10/767,252	
	Filing Date	01/29/2004	
	First Named Inventor	Martin Soika, et al.	
	Art Unit	3721	
	Examiner Name	N/A	
Total Number of Pages in This Submission		Attorney Docket Number	P-US-PR 1092

ENCLOSURES (check all that apply)				
<input type="checkbox"/> Fee Transmittal Form <input type="checkbox"/> Fee Attached <input type="checkbox"/> Amendment / Reply <input type="checkbox"/> After Final <input type="checkbox"/> Affidavits/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input checked="" type="checkbox"/> Information Disclosure Statement <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) <input checked="" type="checkbox"/> Response to Missing Parts/ Incomplete Application <input checked="" type="checkbox"/> Response to Missing Parts under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Request for Refund <input type="checkbox"/> CD, Number of CD(s) _____	<input type="checkbox"/> After Allowance Communication to Group <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communication to Group (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input checked="" type="checkbox"/> Other Enclosure(s) (please identify below): return postcard		
<table border="1"><tr><td>Remarks</td><td>In response to the Notice to File Missing Parts of Non-provisional Application Filing Date Granted dated June 15, 2004, attached is a copy of the Combined Declaration and Power of Attorney for the above-referenced patent application. The Commissioner is hereby authorized to charge \$130 for filing the Declaration to Deposit Account No. 02-2548.</td></tr></table>			Remarks	In response to the Notice to File Missing Parts of Non-provisional Application Filing Date Granted dated June 15, 2004, attached is a copy of the Combined Declaration and Power of Attorney for the above-referenced patent application. The Commissioner is hereby authorized to charge \$130 for filing the Declaration to Deposit Account No. 02-2548.
Remarks	In response to the Notice to File Missing Parts of Non-provisional Application Filing Date Granted dated June 15, 2004, attached is a copy of the Combined Declaration and Power of Attorney for the above-referenced patent application. The Commissioner is hereby authorized to charge \$130 for filing the Declaration to Deposit Account No. 02-2548.			
SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT				
Firm or Individual name	Michael P. Leary			
Signature				
Date	June 24, 2004			

CERTIFICATE OF MAILING			
I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below.			
Typed or printed name	Rebecca A. Sigler		
Signature		Date	June 24, 2004

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

USA

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed *Am. S. Jones*

Dated 19 November 2003

THIS PAGE BLANK (USPTO)

Patents Form 1/77


Pat. Act 1977
(Rule 16)



31JAN03 E781348-1 000223
P01/7700 0.00-0302206.8

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference
P-UK-P21092
2. Patent application number
(The Patent Office will fill in this part)
0302206.8
3. Full name, address and postcode of the or of each applicant (underline all surnames)
BLACK & DECKER INC
DRUMMOND PLAZA OFFICE PARK
1423 KIRKWOOD HIGHWAY
NEWARK, DELAWARE 1
U.S.A.
Patents ADP number (if you know it)
If the applicant is a corporate body, give the country/state of its incorporation
DELAWARE, U.S.A. 341216083
4. Title of the invention
TOOL
5. Name of your agent (if you have one)
REGAN-ADDIS H, BELL I S, SHAYA D.M.
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)
BLACK & DECKER PATENT DEPT
210 BATH ROAD
SLOUGH, BERKSHIRE
SL1 3YD, U.K.
Patents ADP number (if you know it)
8130148001
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:
 - a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
 See note (d))
YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form —

Description 8 ✓

Claim(s) 3 ✓

Abstract 1 ✓

Drawing(s) 2 + 2 RW

10. If you are also filing any of the following, state how many against each item.

Priority documents —

Translations of priority documents —

Statement of inventorship and right to grant of a patent (Patents Form 7/77) —

Request for preliminary examination and search (Patents Form 9/77) ✓

Request for substantive examination (Patents Form 10/77) —

Any other documents (please specify)

COVER LETTER, FEE SHEET ✓

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Heather R. Addis 30/1/03

12. Name and daytime telephone number of person to contact in the United Kingdom

01663 719020


HEATHER RECAN-ADDIS

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.




7/77
Search

Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road
Newport
Gwent
NP10 8QQ

1.	Your reference	P-UK-PR1092
2.	Patent application number (if you know it)	0302206.8
3.	Full name of the or of each applicant	19APR03 B129789-1 C68900 BLACK & DECKER INC P07/7700 0.00-0302206.8
4.	Title of the invention	TOOL
5.	State how the applicant(s) derived the right from the inventor(s) to be granted a patent	By virtue of employment and in accordance with Section 39 of The Patents Act 1997
6.	How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c))	NONE
7.	I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to. Signature  Date: 17 April 2003	
8.	Name and daytime telephone number of person to contact in the United Kingdom	MAUREEN O'REILLY 01753 500676

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

MARTIN SOIKA
IN DER EISENBACH 23
65510 IDSTEIN
GERMANY

805467001

Patents ADP number (if you know it):

RAINER HERTING
EINHAUSSTR. 17
56459 LANGENHAHN
GERMANY

6051650001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?

TOOL

The present invention relates to hand held tools powered by an electric motor, in particular drilling and/or hammering tools.

In such tools an electric motor may be used for providing a rotary drive to a spindle drive mechanism for rotatingly driving a tool and/or bit of the tool and/or for providing a rotary drive to a hammer drive mechanism for providing repeated impacts to the tool and/or bit. The motor may be assembled as a motor sub-assembly in a housing portion, with for example, a motor cooling fan. The motor sub-assembly may then be fixed with respect to a gear casing portion of the tool which may house the spindle drive mechanism and/or hammer drive mechanism of the tool. The arrangement for fixing the motor with respect to the gear casing will need to be robust, should enable efficient rotary drive transmission between an armature shaft of the motor to the drive mechanisms of the tool, should provide adequate sealing of the gear casing to prevent ingress of dust, for example from a motor cooling airflow and should provide adequate fixing of a bearing of the armature shaft with respect to the gear casing.

Traditionally separate components may be used for providing the multiple functions described above, which may lead to a fairly complex arrangement of components and may lead to a relatively complex assembly process for assembling the motor sub-assembly with respect to the gear casing sub-assembly.

The present invention aims to provide a hand held electrically powered tool in which the fixing of the motor sub-assembly with respect to the gear casing is simplified, both in terms of the components used and of the assembly process required.

According to a first aspect of the present invention there is provided a hand held electrically powered tool, comprising:

- a gear casing for housing a drive mechanism of the tool, which gear casing comprises an entrance;

- a motor including an armature sub-assembly comprising an armature shaft having a first end at which a pinion is formed for engaging the drive mechanism,
- a motor plate having a central opening mounted around the armature shaft

adjacent said first end and a first armature shaft bearing located between the motor plate and the pinion, wherein said pinion and bearing are received in said entrance;

characterised in that a moulded on resilient sealing ring is located around the central opening through the motor plate for sealing between the motor plate and the armature shaft and a moulded on resilient O-ring is located on the face of the motor plate facing the bearing for engaging the outer race of said bearing.

According to a second aspect of the present invention there is provided an armature sub-assembly for a motor of a hand held electrically powered tool comprising an armature shaft having a first end at which a pinion is formed, a motor plate having a central opening mounted around the armature shaft adjacent said first end and a first armature shaft bearing located between the motor plate and the pinion, characterised in that a moulded on resilient sealing ring is located around the central opening through the motor plate for sealing between the motor plate and the armature shaft and a moulded on resilient O-ring is located on the face of the motor plate facing the bearing for engaging the outer race of said bearing.

By moulding on the seal and O-ring, separate components are not required for the functions of sealing between the motor plate and armature shaft and for the rotational fixing of the outer race of the armature bearing. With fewer components assembly of the tool or sub-assembly is correspondingly simplified. Also, by moulding the rings on, the rings are accurately located in the desired position, which may not always be the case with separately assembled rings.

The motor is housed in a motor housing portion and the motor plate may be sandwiched between the motor housing portion and the bearing when the motor is fixed with respect to the gear casing. In particular, fixing members, such as screws or bolts may pass through receiving holes in the gear casing and the motor housing portion and through recesses in the motor plate for fixing the motor with respect to the gear casing.

According to one embodiment of the present invention, the resilient sealing ring is moulded directly onto the motor plate. In this case the resilient sealing ring may have a first portion which is moulded onto the motor plate and a second portion which depends

from the first portion and forms a seal against the armature shaft. The first portion may have an L-shaped radial cross-section so that it can be moulded to the edge of the central hole in the motor plate and a portion of a face of the motor plate adjacent the hole and the second portion may have a V-shaped radial cross-section and may depend from the outside corner of the L-shaped portion so that an end of the V-shaped portion remote from the L-shaped portion bears against the armature shaft. Similarly, the resilient O-ring may be moulded directly onto the motor plate. In this case a single component comprising the motor plate with the resilient ring and O-ring moulded onto it can serve several functions.

In an alternative embodiment, the resilient sealing ring and the resilient O-ring are moulded onto a metal ring which metal ring may be fitted within the central opening of the motor plate. This embodiment has the advantage of it being simpler to mould the moulded on rings onto the metal ring than directly onto the motor plate. However, an additional component, the metal ring, is required and an additional assembly step, the fitting of the metal ring to the motor plate, is also required. The metal ring may have an axially extending portion and the resilient sealing ring may comprises a first portion moulded over the axially extending portion and a second portion depending from the first portion and forming a seal against the armature shaft. In this case, the first portion of the resilient sealing ring may have a U-shaped radial cross-section which may fit over an end of the axially extending portion of the metal ring and the second portion may have a V-shaped radial cross-section and depend from the radially innermost corner of the U-shaped portion. The first portion may help to form a deformable releasable coupling between the metal ring and the motor plate. The metal ring may also have a radially outwardly extending portion or flange and the resilient O-ring may be formed on a face of the radially extending portion.

A fan may be mounted for rotation on the armature shaft and the motor plate may be located adjacent the fan, so that the plate forms part of a chamber for the fan and through holes may be formed in the motor plate which act as inlets to the fan.

When the motor is fixed with respect to the gear casing the resilient O-ring may preferably be supported on its radially outer surface by a surface of the entrance to the bearing housing.

An embodiment of a hammer and an armature sub-assembly according to the present invention will now be described by way of example, with reference to the accompanying drawings, in which:

5 Figure 1 shows a side view of a rotary hammer according to the present invention;

Figure 2 shows a longitudinal cross-section through the motor housing portion of the hammer of Figure 1 showing the motor of the hammer;

Figure 3 shows a perspective view of the motor housing portion of the hammer of Figure 1;

10 Figure 4A shows a radial cross-section through the motor plate of the motor of the hammer of Figure 1 with a directly moulded on O-ring and seal;

Figure 4B shows a perspective view of the motor plate of Figure 4A; and

15 Figure 5 shows a radial cross-section of a central portion of an alternative design of motor plate, to that shown in Figures 4A and 4B having a ring sub-assembly comprising a moulded on O-ring and seal.

The hand held electrically powered hammer shown in Figures 1 to 3 has a housing comprising a motor housing portion (2) within which an electric motor (4) of the hammer is housed. The motor (4) is aligned with its longitudinal axis (5) perpendicular to the longitudinal axis (3) of a spindle (not shown) of the hammer. The present invention is equally applicable to a hammer in which the axis of the longitudinal motor is parallel, or at any other angle, to the longitudinal axis (3) of the spindle of the hammer.

A tool holder (26) is located at the forward end of the spindle. A tool or bit (not shown) can be non-rotatably and releasably fitted within the tool holder so as to allow limited reciprocation of the tool or bit with respect to the tool holder. The hammer has a rear handle (18) in which an on/off trigger (20) is located for actuating a switch for actuating power supply to the motor (4). The armature shaft (8) of the motor has a pinion (24) at

its end closest to the spindle axis (3), which mates with a bevel gear (10) of an intermediate shaft (12). A wobble drive arrangement (14) is used for converting a rotary drive from the intermediate shaft (12) to a reciprocating drive of an air cushion hammering mechanism, as is known in the art, for generating repeated impacts on the rearward end of the tool or bit. The intermediate shaft may also transmit a rotary drive to the spindle and thereby to the tool or bit mounted within the spindle, as is known in the art. The intermediate shaft (12) and wobble drive arrangement (14) are housed in a metal gear casing (30). A mode change arrangement, actuated by a mode change knob (50), is provided for enabling the selective engagement of rotary drive to the spindle and/or selective actuation of the air cushion hammering mechanism so that the hammer can be operated in a drilling only mode, a hammering only mode and/or a combination rotary hammering mode, as is well known in the art.

The motor (4) comprises an armature sub-assembly, which comprises an armature (6), armature shaft (8) with a pinion (24) formed at its upper end, a motor fan (20), armature upper and lower bearings (22, 24), an upper sealing ring (32), a lower spacer ring (34) and a motor plate (16). The motor plate (16), shown in more detail in Figures 4A and 4B, is formed with a central through hole (42) through which an increased diameter portion of the armature shaft passes. The motor plate is axially secured on the armature shaft (8) by the forward bearing (22) which is press fitted onto the armature shaft (8) against a shoulder (28) formed thereon. The metal gear casing (30) is formed with a circular through hole for receiving the motor pinion (24), upper sealing ring (32) and the upper bearing (22). The upper sealing ring (32) fits within a reduced diameter portion of the through hole in the gear casing (30) and rotates with the armature shaft, to provide sealing between the gear casing (30) and the motor (4). When the upper portion of the armature sub-assembly is fitted into the through hole, the upper bearing (22) is received with tight tolerances within an increased diameter portion of the through hole in the gear casing (30) and the forward end of the forward bearing (22) abuts a shoulder formed by the reduced diameter portion of the through hole. The motor plate (16) is formed with a set of through holes (40) which form air inlets to the adjacent radial armature fan (20), which fan rotates with the armature shaft (8) so as to generate a cooling airflow. The motor plate (16) forms an upper wall of a chamber for the fan (20).

Screw bosses (36) are formed in the motor housing portion (2) of the hammer housing. The motor plate (16) is formed with four recesses (34) which fit around the bosses (36).

The lower side of the motor plate (16) abuts a forward edge of a motor casing portion (44). The gear casing (30) is formed with four screw receiving holes (not shown) which are aligned with the screw bosses (36) in the motor housing portion (2). Screws pass through the screw receiving holes in the gear casing, the screw bosses (36) in the motor housing portion (2) and thus through the recesses (34) in the motor plate (16). In this way the motor plate is axially fixed between the forward edge of the motor casing portion (44) and a rearward edge of the outer race of the forward bearing (22) and is rotationally fixed with respect to the hammer housing arrangement via the engagement of the bosses (36) in the recesses (34) to thereby fix the armature sub-assembly with respect to the gear casing (30) and the motor housing (2).

As shown in Figures 4A and 4B, according to a first embodiment of the present invention, a ring shaped resilient seal (38) is moulded directly onto the rim of the through hole (42) in the motor plate (16) and a resilient O-ring (46) is moulded directly onto the surface of the motor plate facing the bearing housing.

The moulded seal (38) seals between the through hole (42) in the motor plate (16) and the rotatable armature shaft (8) in order to seal dust out of the gear casing (30). This is important because the cooling airflow for the motor (4), in which airflow some dust may be entrained, flows over the lower side of the seal (38) and through the inlets (40) formed in the motor plate (16) to the fan (20). The seal (38) has a radial cross-section as shown in Figure 4A, with an L-shaped cross-sectioned portion that abuts and is moulded to the inner surface of the central hole (42) and a part of the lower surface of the plate (16) surrounding the central hole (42) and a V-shaped cross-sectioned portion which extends from the outer corner of the L-shaped portion. The end of the V-shaped portion remote from the L-shaped portion is urged as a result of the resilient characteristic of the material from which the seal (18) is made against the increased diameter portion of the armature shaft.

The inwardly facing face of the moulded O-ring (46) resiliently abuts the outer race of the upper bearing (22) acting so as to prevent the outer race from rotating with the inner race of the bearing (22). When the motor (4) is fixed with respect to the gear casing (30), the surface of an increased diameter portion of the through hole in the gear casing (30) receives the upper portion of the O-ring (46) and supports the O-ring (46) against the outer race of the upper bearing (22).

Thus, according to the first embodiment of the present invention the three functions of fixing the armature sub-assembly with respect to the gear casing (30) and the motor (4), of sealing between the motor plate (16) and the armature shaft (8) and of fixing the outer race of the upper bearing (22) of the armature shaft are achieved using a single component comprising the motor plate (16) with the resilient seal (38) and O-ring (46) moulded onto it.

An alternative to the motor plate (16) is shown in Figure 5. The motor plate (116) is formed with a central through hole (142), inlet holes (140) to the fan (20) and boss receiving recesses (134) for receiving screw bosses (36). However, the resilient seal (138) and resilient O-ring (146) (equivalent to the seal (38) and O-ring (46) respectively in the Figure 4A and 4B embodiment) are moulded onto a metal ring (148). The metal ring has an L-shaped radial cross-section with a first radially extending portion which (when the metal ring (148) is fitted to the motor plate (116)) abuts the upper face of the motor plate and with a second axially extending portion which extends axially downwardly of the radially extending portion of the metal ring. The seal (138) has a U-shaped cross-sectioned fixing portion which is moulded over the axially extending portion of the metal ring (148) and a V-shaped cross-sectioned sealing portion which extends from the inner corner of the U-shaped portion.

The metal ring (148) with the seal (138) and O-ring (146) is fitted into the central hole (142) of the motor plate (116), before the motor plate (116) is fitted over the armature shaft (8). A part (150) of the U-shaped portion of the resilient seal (138) is wedged between the rim of the through hole (142) of the motor plate (116) and the axially extending portion of the metal ring (148) and acts to provide a deformable releasable fixing between the metal ring (148) and the motor plate (116). The upper motor bearing (22) is press fit onto the upper end of the armature shaft (8) against the shoulder (28) to thereby trap the metal ring (148) between the motor plate (116) and the bearing (22) to form a permanent fixing of the metal ring (148) with respect to the motor plate (116). The O-ring (146) abuts the outer race of the bearing (22) to prevent its rotation. The motor plate (116) is fixed with respect to the gear casing (30) and the motor housing portion (2) in the same way as is described above in relation to the embodiments of Figures 4A and 4B.

The O-ring (46, 146) and the seal (38, 138) may be made of an elastomeric material. The motor plate (16, 116) and the metal ring (148) may be made of steel or stainless steel.

Claims:

1. A hand held electrically powered tool, comprising:
 - a gear casing (30) for housing a drive mechanism of the tool, which gear casing comprises an entrance;
 - a motor (4) including an armature sub-assembly comprising an armature shaft (8) having a first end at which a pinion (24) is formed for engaging the drive mechanism, a motor plate (16, 116) having a central opening (42, 142) mounted around the armature shaft adjacent said first end and a first armature shaft bearing (22) located between the motor plate and the pinion, wherein said pinion and bearing are received in said entrance;

characterised in that a moulded on resilient sealing ring (38, 138) is located around the central opening through the motor plate for sealing between the motor plate and the armature shaft and a moulded on resilient O-ring (46, 146) is located on the face of the motor plate facing the bearing (22) for engaging the outer race of said bearing.
2. A tool according to claim 1 wherein the motor is housed in a motor housing portion (2) and the motor plate (16, 116) is sandwiched between the motor housing portion (2) and the bearing (22) when the motor is fixed with respect to the gear casing.
3. A tool according to claim 1 or claim 2 wherein fixing members, pass through receiving holes in the gear casing (30) and the motor housing portion (2) and through recesses (34) in the motor plate for fixing the motor (4) with respect to the gear casing (30).
4. A tool according to any one of claims 1 to 3 wherein the resilient sealing ring (38) is moulded directly onto the motor plate (16).
5. A tool according to claim 4 wherein the resilient sealing ring has a first portion which is moulded onto the motor plate and a second portion which depends from the first portion and forms a seal against the armature shaft (8).

6. A tool according to claim 5 wherein the first portion has an L-shaped radial cross-section and the second portion has a V-shaped radial cross-section and depends from the outside corner of the L-shaped portion.
7. A tool according to any one of claims 1 to 6 wherein the resilient O-ring (46) is moulded directly onto the motor plate (16).
8. A tool according to any one of claims 1 to 3 wherein the resilient sealing ring (138) and the resilient O-ring (146) are moulded onto a metal ring (148) which metal ring fits within the central opening (142) of the motor plate (116).
9. A tool according to claim 8 wherein the metal ring (148) has an axially extending portion and the resilient sealing ring (138) comprises a first portion moulded over the axially extending portion and a second portion which depends from the first portion and forms a seal against the armature shaft (8).
10. A tool according to claim 8 wherein the first portion of the resilient sealing ring (138) has a U-shaped radial cross-section and the second portion has a V-shaped radial cross-section and depends from the radially inner corner of the U-shaped portion.
11. A tool according to any one of claims 8 to 10 wherein the metal ring (148) has a radially outwardly extending portion and the resilient O-ring (146) is formed on a face of the radially extending portion.
12. A tool according to any one of the preceding claims wherein the motor plate (16, 116) is located adjacent a fan (20), which fan is mounted to rotate with the armature shaft, so that the plate forms part of a chamber for the fan and through holes (40) are formed in the motor plate which act as inlets to the fan.
13. A tool according to any one of the preceding claims wherein the resilient O-ring (46, 146) is supported on its radially outer surface by a surface of the entrance to the bearing housing (30).
14. A tool substantially as hereinbefore described with reference to any one of the accompanying Figures.

15. An armature sub-assembly for a motor (4) of a hand held electrically powered tool comprising an armature shaft (8) having a first end at which a pinion (24) is formed, a motor plate (16, 116) having a central opening (42, 142) mounted around the armature shaft adjacent said first end and a first armature shaft bearing (22) located between the motor plate and the pinion, characterised in that a moulded on resilient sealing ring (38, 138) is located around the central opening though the motor plate for sealing between the motor plate and the armature shaft and a moulded on resilient O-ring (46, 146) is located on the face of the motor plate facing the bearing (22) for engaging the outer race of said bearing.
16. A sub-assembly according to claim 15 wherein the resilient sealing ring (38) is moulded directly onto the motor plate (16).
17. A sub-assembly according to claim 15 or 16 wherein the resilient O-ring (46) is moulded directly onto the motor plate (16).
18. A sub-assembly according to claim 15 wherein the resilient sealing ring (138) and the resilient O-ring (146) are moulded onto a metal ring (148) which metal ring fits within the central opening (142) of the motor plate (116).
19. A sub-assembly according to any one of claims 15 to 18, additionally including a fan (20) mounted on the armature shaft to rotate with the shaft, wherein the motor plate (16, 116) is located adjacent the fan (20) so that the plate forms part of a chamber for the fan and through holes (40) are formed in the motor plate which act as inlets to the fan.
20. An armature sub-assembly for a motor (4) of a hand held electrically powered tool substantially as hereinbefore described with reference to any one of the accompanying Figures.

ABSTRACT

TOOL

A hand held electrically powered tool, in particular a drilling and/or hammering tool, comprising a gear casing (30) for housing a drive mechanism of the tool, which gear casing comprises an entrance. The motor (4) of the tool includes an armature sub-assembly comprising an armature shaft (8) having a first end at which a pinion (24) is formed for engaging the drive mechanism. A motor plate (16, 116) for fixing the gear casing with respect to the motor is provided having a central opening (42, 142) and is mounted around the armature shaft adjacent said first end and a first armature shaft bearing (22) located between the motor plate and the pinion. When the gear casing and motor are assembled the pinion and bearing are received in the entrance to the gear casing. A moulded on resilient sealing ring (38, 138) is located around the central opening through the motor plate for sealing between the motor plate and the armature shaft and a moulded on resilient O-ring (46, 146) is located on the face of the motor plate facing the bearing (22) for engaging the outer race of said bearing.

Figure 2.




Fig. 1.




Fig. 2

THIS PAGE BLANK (USPTO)




FIG 4B




FIG 4A




FIG 3




FIG 5

THIS PAGE BLANK (USPTO)